



Тип наконечника по ГОСТ 7386-80	Сечение провода	Класс жилы
2,5 - (3,4,5,6) - 2,6	2,5	3,4,5,6
	4	1,2,3,4
4 - (4,5,6) - 3	4	5
	6	1
6 - (4,5,6) - 4	4	6
	6	2,3,4,5
	10	1
10 - (5,6,8) - 5	10	2,3,4
	16	1
16 - (6,8) - 6	10	5,6
	16	2,3
	25	1
25 - (6,8) - 7	16	4,5,6
	25	2
	35	1
25 - (6,8,10) - 8	25	3,4,5,6
	35	2
35 - (8,10) - 9	35	3,4
	50	1
	35 - (8,10,12) - 10	35
50 - (8,10,12) - 11	50	2
	70	3,4
50 - (8,10,12) - 12	50	1,2
	70	5,6
70 - (10,12) - 13	70	3,4,5,6
	95	1
	70	5
95 - (10,12) - 15	95	2,3,4,6
	120	1,2
	95	5
95 - (10,12) - 16	120	1,2
	120 - (12,16) - 17	120
120 - (12,16) - 18	120	6
	185	1,2
	150 - (12,16) - 19	150
150 - (12,16) - 20	185	3
	150	4,5
185 - (12,16,21) - 21	240	1
	185	4,6
	240	1,2
185 - (16,20) - 23	185	5
	300	1,2
	240 - (16,20) - 24	240